

 **MENNEKES®**

Plugs for the world

TOP-Types.  
Products for daily use.



UK / IRL

# Contact persons at MENNEKES in UK

## Management Team



**Christopher Stockdale**  
National Sales Manager  
Tel. 01689 881605  
Fax 01689 873649  
christopher.stockdale@mennekes.co.uk



**Andrea Garte**  
Director International Sales  
Tel. 01689 833522  
Fax 01689 873649  
andrea.garte@mennekes.de



**Christopher Mennekes**  
Managing Director  
Tel. 01689 881600  
Fax 01689 873649  
christopher.mennekes@mennekes.co.uk



**Melvin Johnson**  
Works Manager  
Tel. 01689 881603  
Fax 01689 833378  
mel.johnson@mennekes.co.uk

## Sales Office Team



**Sheila Carpenter**  
Marketing and Sales  
Tel. 01689 881602  
Fax 01689 873649  
sheilacarpenter@mennekes.co.uk



**Roy Choules**  
Technical Sales  
Tel. 01689 881609  
Fax 01689 833378  
roy.choules@mennekes.co.uk



**Julia Ray**  
Sales Co-ordinator  
Tel. 01689 881608  
Fax 01689 833378  
julia.ray@mennekes.co.uk



**Russell Massey**  
Sales Co-ordinator  
Tel. 01689 833522  
Fax 01689 833378  
russell.massey@mennekes.co.uk

## Regional Sales Engineers

### North and Scotland



**Dean Bailey**  
Tel. 01689 833522  
Mobile 07950 394015  
Fax 01689 833378  
dean.bailey@mennekes.co.uk

### North, Wales and Northern Ireland



**Stuart Green**  
Tel. 01689 833522  
Mobile 07793 220931  
Fax 01689 833378  
stuart.green@mennekes.co.uk

### Midlands



**Ian Whitby-Smith**  
Tel. 01689 833522  
Mobile 07711 054819  
Fax 01689 833378  
ian.whitby-smith@mennekes.co.uk

### South









**Paul Bristow**  
Tel. 01689 833522  
Mobile 07985 260180  
Fax 01689 833378  
paul.bristow@mennekes.co.uk















# Wall mounted sockets

	<b>Wall mounted socket</b> top entry  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1177	1178	
		16	4		1267	1268
		16	5			1
		32	3	1368	1369	1370
		32	4		1372	1373
		32	5			2
	<b>Wall mounted socket</b> top and bottom entry 32A: optionally fitted with auxiliary contact (Part no. 41000)  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	100	101	102
		16	4	103	104	105
		16	5	109	110	111
		32	3	1420	1421	1422
		32	4	1423	1424	1425
		32	5	1555	1556	1557
	<b>Wall mounted socket</b> SoftCONTACT, top and bottom entry Products with pilot contact: Part no. + index "P"  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	1136A	1137A	
		63	4		1140A	1141A
		63	5		1144A	1145A
	<b>Wall mounted socket</b> top and bottom entry Optionally fitted with auxiliary contact (Part no. 41000)  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1193	1192	1211
		16	4	1194	1195	1196
		16	5	1198	1199	1200
		32	3	1201	1202	1203
		32	4	1204	1205	1206
		32	5	1208	1209	1210
	<b>Wall mounted socket</b> SoftCONTACT, top and bottom entry Products with pilot contact: Part no. + index "P"  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	856	128A	129A
		63	4	130A	131A	132A
		63	5	134A	135A	136A
	<b>Wall mounted socket</b> top and bottom entry Products with pilot contact: Part no. + index "P"  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		125	3	on request		
		125	4	137	138	139
		125	5	141	142	143

	<b>Wall mounted socket</b> screwless, with TwinCONTACT, top entry	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
	⚠ IP 44	16	3	1340	1341	
		16	4		1342	1343
		16	5			31
		32	3	1345	1346	
		32	4		1347	1348
		32	5			32
	<b>Wall mounted socket</b> screwless, with TwinCONTACT, top and bottom entry	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
	⚠ IP 44	16	3	1719	1720	1721
		16	4		1723	1724
		16	5		1730	3331
	<b>Wall mounted socket</b> screwless, with TwinCONTACT, top and bottom entry Optionally fitted with auxiliary contact (Part no. 41000)	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
	⚠ IP 44	16	3	1750	1751	418
		16	4	1755	1756	419
		16	5	1851	420	1852
		32	4	1855	1856	421
		32	5	1860	1861	422
	<b>Wall mounted socket</b> screwless, with TwinCONTACT, top and bottom entry Optionally fitted with auxiliary contact (Part no. 41000)	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
	⚡ IP 67	16	3	1867	241	1868
		16	4	1870	1871	242
		16	5	1875	1876	200
		32	3	1877	243	1878
		32	4	1879	1880	244
		32	5	1884	1885	245
	<b>Double box</b> screwless, with TwinCONTACT, CEE and socket British standard 13A, 2p+E, 230V in one enclosure Also available with French/Belgian, Danish and Swiss standard.	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
	⚠ IP 44	16	4		1647GB	1648GB
		16	5			1649GB
					with fuse holder, max. 10 A H	
		16	5			1650GB
		32	5			1651GB
	<b>Auxiliary contact</b> for standard sockets and panel mounted sockets 16A and 32A	<b>Part number</b>				
		41000				

## Wall mounted sockets

	<b>Wall mounted socket</b> switched, with mechanical DUO-interlock  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	7010A	7002A	
		16	4	5457A	5099A	5100A
		16	5	5459A	5102A	5103A
		32	3	5743A	5696A	
		32	4	5460A	5104A	5105A
		32	5	5462A	5107A	5108A
	<b>Wall mounted socket</b> SoftCONTACT, switched, with mechanical DUO-interlock  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	6569	6571	
		63	4		5955A	5956A
		63	5			5959A
	<b>Wall mounted socket</b> switched, with mechanical DUO-interlock  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	7273	7274	
		16	4		7380	7275
		16	5			7276
	<b>Wall mounted socket</b> switched, with mechanical DUO-interlock  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	7011A	7012A	
		16	4		5599A	5600A
		16	5		5602A	5603A
		32	3	5924A	5793A	
		32	4		5604A	5605A
		32	5		5607A	5608A
	<b>Wall mounted socket</b> SoftCONTACT, switched, with mechanical DUO-interlock  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	5925A	5911A	
		63	4		5109A	5110A
		63	5		5112A	5113A
	<b>Wall mounted socket</b> TorsionSpringCONTACT, switched, with mechanical DUO-interlock  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		125	3	7060	7000	
		125	4		5887A	5691A
		125	5		5888A	5692A

	<b>Wall mounted socket</b> switched, with mechanical DUO-interlock	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	7277	7278	
		16	4		7381	7279
		16	5			7280
☹ IP 67						
	<b>Wall mounted socket</b> protected by 1 RCD 30 mA	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3		7148MEL	
		16	4			7149MEL
		16	5			7150MEL
		32	3			
		32	4			7151MEL
32	5			7152MEL		
☹ IP 67						
	<b>Wall mounted socket</b> protected by 1 RCD 30 mA	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	52111	24193	
		16	4			24194
		16	5			24195
		32	3	52120	24196	
		32	4			24197
32	5			24198		
⚠ IP 44						
	<b>Wall mounted socket</b> protected with 1 "C"-type MCB	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	52170	52171	
		16	4			52172
		16	5			52173
		32	3	52174	52175	
		32	4			52176
32	5			52177		
⚠ IP 44						
	<b>Wall mounted socket</b> protected by 1 RCD 30 mA and 1 "C"-type MCB	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	52131	24233	
		16	4			24234
		16	5			24235
		32	3	52140	24236	
		32	4			24237
32	5			24238		
⚠ IP 44						
	<b>AMAXX® combination unit</b> protected by 1 RCD 30 mA	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	920694	921036	
		16	4			920695
		16	5			920683
		32	3	920699	920696	
		32	4			920673
32	5			921037		
☹ IP 67						

## Wall mounted sockets



### AMAXX® combination unit

protected by 1 RCD 30 mA  
MCB on request.

☼☼ IP 67

A	P	110V	230V	400V
63	3		920666	
63	4			920668
63	5			920670



### AMAXX® combination unit

switched, with mechanical DUO interlock,  
protected by 1 RCD 30 mA  
MCB on request.

☼☼ IP 67

A	P	110V	230V	400V
16	3	921380	922452	
16	4			922517
16	5			922453
32	3	922519	921442	
32	4			922518
32	5			922218



### AMAXX® combination unit

protected by 1 RCD 30 mA  
MCB on request.

☼☼ IP 67

A	P	110V	230V	400V
16	3	920700	920649	
16	4			920791
16	5			920278
32	3		921160	
32	4			
32	5			921953



### AMAXX® combination unit

protected by 1 RCD 30 mA  
and 1 "C"-type MCB

☼☼ IP 67

A	P	110V	230V	400V
16	3	920713	920714	
16	4			
16	5			
32	3			
32	4			
32	5			



### AMAXX® combination unit

resistant to chemicals, made of AMELAN®,  
protected by 1 RCD 30 mA  
MCB on request.

☼☼ IP 67

A	P	110V	230V	400V
16	3		920818	
16	4			920819
16	5			920820
32	3		921022	
32	4			921023
32	5			921024



### AMAXX® combination unit

resistant to chemicals, made of AMELAN®,  
protected by 1 RCD 30 mA  
MCB on request.

☼☼ IP 67

A	P	110V	230V	400V
63	3		922520	
63	4			922521
63	5			922522



**Wall mounted socket**

switched, with mechanical DUO-interlock, protected by 1 RCD 30 mA

▲ IP 44

A	P	110V	230V	400V
16	3	52210	51392	
16	4			24202
16	5			24203
32	3	52211	24204	
32	4			24205
32	5			24206

**Wall mounted socket**

switched, with mechanical DUO-interlock, protected by 1 RCD 30 mA and 1 "C"-type MCB

▲ IP 44

A	P	110V	230V	400V
16	3	52213	51393	
16	4			24242
16	5			24243
32	3	52214	24244	
32	4			24245
32	5			24246

**Wall mounted socket**

SoftCONTACT, switched, with mechanical DUO-interlock, protected by 1 RCD 30 mA

▲ IP 44

A	P	110V	230V	400V
63	3	52212	24207	
63	4			24208
63	5			24209

**Wall mounted socket**

SoftCONTACT, switched, with mechanical DUO-interlock, protected by 1 RCD 30 mA and 1 "C"-type MCB

▲▲ IP 67

A	P	110V	230V	400V
63	3	52215	24247	
63	4			24248
63	5			24249

**Wall mounted socket**

TorsionSpringCONTACT, switched, with mechanical DUO-interlock, protected by 1 RCD 30 mA

Add-on equipment is required to install a padlock.

▲▲ IP 67

A	P	110V	230V	400V
125	3		52030	
125	4			52031
125	5			52032

**Wall mounted socket**







TorsionSpringCONTACT, switched, with mechanical DUO-interlock, protected by 1 RCD 100 mA







Add-on equipment is required to install a padlock.

▲▲ IP 67

A	P	110V	230V	400V
125	3		52033	
125	4			52034
125	5			52035







## Panel mounted sockets

	<b>Panel mounted socket</b> flange 75 x 75 mm, straight	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1365	1366	1367
		16	4	1388	1389	1390
		16	5	1384	1386	1385
		32	3	1394	1395	1396
		32	4	1397	1398	1399
		32	5	3449	3454	3451
	▲ IP 44					
	<b>Panel mounted socket</b> flange 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination, 32A: optionally fitted with auxiliary contact (Part no. 41000)	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1462	1463	1464
		16	4	1465	1466	1467
		16	5	1471	1472	1473
		32	3	1491	1492	1493
		32	4	1494	1495	1496
		32	5	1498	1499	1500
	▲ IP 44					
	<b>Panel mounted socket</b> flange 16A: 75 x 75 mm, 32A: 85 x 75 mm, straight	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	217A	218A	219A
		16	4	220A	221A	222A
		16	5	226A	227A	228A
		32	3	229A	230A	231A
		32	4	232A	233A	234A
		32	5	238A	239A	240A
	▲▲ IP 67					
	<b>Panel mounted socket</b> flange 63A: 107 x 100 mm, 125A: 130 x 130 mm, straight, 63A: SoftCONTACT, 125A: TorsionSpringCONTACT, products with pilot contact: Part no. + index P.	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	1263A	1264A	1265A
		63	4	1122A	1123A	1124A
		63	5	1126A	1127A	1128A
		125	3		3380	
		125	4	1455	1456	1457
		125	5	1459	1460	1461
	▲▲ IP 67					
	<b>Panel mounted socket</b> flange 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination, 32A: optionally fitted with auxiliary contact (Part no. 41000)	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1474	1475	1476
		16	4	1477	1478	1479
		16	5	1483	1484	1485
		32	3	1501	1502	1503
		32	4	1504	1505	1506
		32	5	1489	1490	1551
	▲▲ IP 67					
	<b>Panel mounted socket</b> flange 63A: 110 x 106 mm, 20° inclination, 125A: 114 x 110 mm, 15° inclination, 63A: SoftCONTACT, 125A: TorsionSpringCONTACT	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	2179A	2180A	2181A
		63	4	203A	204A	205A
		63	5	207A	208A	209A
		125	3		3575	
		125	4	210A	211A	212A
		125	5	214A	215A	216A
	▲▲ IP 67					

	<b>Panel mounted socket</b> screwless, with TwinCONTACT, flange: 75 x 75 mm, straight	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1667	1668	1669
		16	4	1672	1673	1674
		16	5	1678	1679	3385
		32	3	1786	1787	1788
		32	4	1789	1790	1791
		32	5	1795	1796	1797
	<b>Panel mounted socket</b> screwless, with TwinCONTACT, flange 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination, 32A: optionally fitted with auxiliary contact	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1631	1632	1633
		16	4	1636	1637	1638
		16	5	1642	1643	3473
		32	3	1733	1734	1735
		32	4	1738	1739	1740
		32	5	1744	1745	1746
	<b>Panel mounted socket RAPIDO®</b> screwless, with TwinCONTACT, with central locking system, round flange for central fixing, diam. 70 mm	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	4		1133	998
		16	5			907
		32	3	1135	987	
		32	4		1166	988
		32	5			989
	<b>Panel mounted socket</b> screwless, with TwinCONTACT, flange: 16A: 75 x 75 mm, 32A: 85 x 75 mm, straight	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1707	1708	1709
		16	4	1710	1711	1712
		16	5	1716	1717	1131
		32	3	1809	1810	1811
		32	4	1812	1813	1814
		32	5	1818	1819	1820
	<b>Panel mounted socket</b> screwless, with TwinCONTACT, flange: 16A, 3p: 73.5 x 64 mm, 16A, 4 + 5p, 32A: 100 x 92 mm, 20° inclination, 32A: optionally fitted with auxiliary contact (Part no. 41000)	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1700	1701	1702
		16	4		1703	1704
		16	5			3485
		32	3	1801	1802	1803
		32	4		1804	1805
		32	5			1808
	<b>Panel mounted socket</b> screwless, with TwinCONTACT, standard flange dimensions 85 x 85 mm, 20° inclination, optionally fitted with auxiliary contact	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	1158	1168	
		16	4			1169
		16	5			1173
		32	3	3566	3573	
		32	4			3581
		32	5			3590

## Plugs and connectors

	<b>Plug AM-TOP®</b> with screw terminals, single part body, cable gland and sealing, strain relief and protection against kinking  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	247	248	249
		16	4	250	251	252
		16	5	256	257	3
		32	3	259	260	261
		32	4	262	263	264
		32	5	268	269	4
	<b>Plug PowerTOP® Xtra</b> rubberised handle area, highly heat resistant contact carrier, frame terminals, nickel plated contacts, cable gland and sealing, strain relief and protection against kinking  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	13101	13102	
		63	4		13105	13106
		63	5		13111	13112
	<b>Plug AM-TOP®</b> with screw terminals, single part body, cable gland and sealing, strain relief and protection against kinking  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	277	278	279
		16	4	280	281	282
		16	5	286	287	288
		32	3	289	290	291
		32	4	292	293	294
		32	5	298	299	300
	<b>Plug PowerTOP®</b> with external cable grip, highly heat resistant contact carrier and nickel plated contacts  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	3794	3796	3799
		16	4	3807	3811	3809
		16	5	3819	3823	3821
		32	3	3829	3830	3832
		32	4	3839	3844	3841
		32	5	3851	3855	3853
	<b>Plug PowerTOP® Xtra</b> rubberised handle area, highly heat resistant contact carrier, frame terminals, nickel plated contacts, cable gland and sealing, strain relief and protection against kinking  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	13201	13202	13203
		63	4	13204	13205	13206
		63	5	13210	13211	13212
		125	3	13215	13216	
		125	4	13217	13218	13219
		125	5	13223	13224	13225
	<b>Wall mounted inlet</b> cable entry also possible from the rear, knock-out section on the bottom part of the back box  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	331	332	333
		63	4	334	335	336
		63	5	340	341	342
		125	3	343	344	345
		125	4	346	347	348
		125	5	352	353	354

	<b>Connector AM-TOP®</b> with screw terminals, single part body, cable gland and sealing, strain relief and protection against kinking  ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	509	510	511
		16	4	512	513	514
		16	5	518	519	5
		32	3	521	522	523
		32	4	524	525	526
		32	5	530	531	6
	<b>Connector PowerTOP® Xtra</b> SoftCONTACT, rubberised handle area, highly heat resistant contact carrier, frame terminals, cable gland and sealing, strain relief and protection against kinking, products with pilot contact: Part no. + index P ▲ IP 44	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	14101	14102	
		63	4		14105	14106
		63	5		14111	14112
	<b>Connector AM-TOP®</b> with screw terminals, single part body, cable gland and sealing, strain relief and protection against kinking  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	539	540	541
		16	4	542	543	544
		16	5	548	549	550
		32	3	551	552	553
		32	4	554	555	556
		32	5	560	561	562
	<b>Connector PowerTOP®</b> with external cable grip and highly heat resistant contact carrier  ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		16	3	3859	3860	3862
		16	4	3869	3873	3871
		16	5	3879	3883	3881
		32	3	3887	3888	3891
		32	4	3896	3899	3897
		32	5	3905	3909	3907
	<b>Connector PowerTOP® Xtra</b> SoftCONTACT, rubberised handle area, highly heat resistant contact carrier, frame terminals, cable gland and sealing, strain relief and protection against kinking, products with pilot contact: Part no. + index P ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		63	3	14201	14202	14203
		63	4	14204	14205	14206
		63	5	14210	14211	14212
	<b>Connector PowerTOP® Xtra</b> TorsionSpringCONTACT, rubberised handle area, highly heat resistant contact carrier, frame terminals, cable gland and sealing, strain relief and protection against kinking, products with pilot contact: Part no. + index P ▲▲ IP 67	<b>A</b>	<b>P</b>	<b>110V</b>	<b>230V</b>	<b>400V</b>
		125	3	14215	14216	
		125	4	14217	14218	14219
		125	5	14223	14224	14225



## DELTA-BOX

Fitted with: 3 sockets British standard 13A, 2p+E, 230V

Connection: for 1 cable up to 5 x 10 mm<sup>2</sup>

⚠ IP 44

Part no. 9101366



## DELTA-BOX

Fitted with: 3 CEE sockets 16A, 5p, 400V

Connection: for 1 cable up to 5 x 10 mm<sup>2</sup>

⚠ IP 44

Part no. 92917



## Socket strip

Fitted with: 2 CEE sockets 16A, 5p, 400V,

1 socket British standard 13A, 2p+E, 230V

Connection: for 1 cable up to 5 x 10 mm<sup>2</sup>

⚠ IP 44

Part no. 9204474



## Socket strip

Fitted with: 3 CEE sockets 16A, 5p, 400V

Connection: for 1 cable up to 5 x 10 mm<sup>2</sup>

⚠ IP 44

Part no. 96705



## AirKRAFT®

Fitted with: 1 CEE socket 16A, 5p, 400V,

3 sockets British standard 13A, 2p+E, 230V

Connection: for 1 cable up to 5 x 10 mm<sup>2</sup>

The colour code of the cover required should be added to the part no. (red = RO, yellow = GE, silver = SI).

⚠ IP 44

Part no. 9405595



## 3KRAFT®

Fitted with: 1 CEE socket 16A, 5p, 400V,

2 sockets British standard 13A, 2p+E, 230V

Connection: for 1 cable up to 5 x 10 mm<sup>2</sup>

The colour code of the cover required should be added to the part no. (Rot = RO, Gelb = GE, Silber = SI).

⚠ IP 44

Part no. 9403747

**EverGUM made of solid rubber**

Fitted with: 3 CEE sockets 16A, 5p, 400V

With feeder cable: 2 m H07RN-F5G2.5 with CEE-plug 16A, 5p, 400V

⚠ IP 44

**Part no. 70029****EverGUM made of solid rubber**Fitted with: 1 CEE socket 32A, 5p, 400V, 1 CEE socket 16A, 5p, 400V,  
3 sockets British standard 13A, 2p+E, 230V

Fusing: 1 MCB 32A, 3p, C, 2 MCB's 16A, 3p, C, 3 MCB's 16A, 1p, B

Connection: for 2 cables up to 5 x 25 mm<sup>2</sup>

⚠ IP 44

**Part no. 7206191****EverGUM made of solid rubber**Fitted with: 1 CEE socket 63A, 5p, 400V, 1 CEE socket 32A, 5p, 400V,  
1 CEE socket 16A, 5p, 400V, 4 sockets British standard 13A, 2p+E, 230VFusing: 1 MCB 63A, 3p, C, 1 MCB 32A, 3p, C, 1 MCB 16A, 3p, C,  
2 MCB's 16A, 1p, BConnection: for 2 cables up to 5 x 25 mm<sup>2</sup>

⚠ IP 44

**Part no. 7310048****EverGUM made of solid rubber**Fitted with: 1 CEE socket 32A, 5p, 400V, 1 CEE socket 16A, 5p, 400V,  
4 sockets British standard 13A, 2p+E, 230V

Fusing: 1 RCD 40A, 4p, 0.03A, 1 MCB 16A, 3p, C, 2 MCB's 16A, 1p, B

With feeder cable: 2 m H07RN-F5G4 with CEE-plug 32A, 5p, 400V

⚠ IP 44

**Part no. 7415200****EverGUM made of solid rubber**Fitted with: 1 CEE socket 63A, 5p, 400V, 1 CEE socket 32A, 5p, 400V,  
1 CEE socket 16A, 5p, 400V, 4 sockets British standard 13A, 2p+E, 230VFusing: 1 RCD 63A, 4p, 0.03A, 1 MCB 32A, 3p, C, 1 MCB 16A, 3p, C,  
2 MCB's 16A, 1p, B

With feeder cable: 3 m H07RN-F5G10 with CEE-plug 63A, 5p, 400V

⚠ IP 44

**Part no. 7517006****Compact network distributor**Fitted with: 1 data socket Cepex with 2 RJ45 connection module couplings,  
type E-DAT module, port, cat.6, brand BTR, 4 sockets British standard  
13A, 2p+E, 240VCable entry: 2 M 25 at the top, 1 M 25 at the bottom,  
1 M 25 3 x 5-7 at the bottom

⚠ IP 44

**Part no. 8310790**

**Made in Germany**

**MENNEKES®**

Plugs for the world

Refer to our brochures and catalogues to keep up to date. Download the latest versions from our website in practical PDF format or request print copies by phone or E-Mail.



Catalogue UK/IRL



**AMAXX® Evolution.**  
Receptacle combinations  
for Energy, Industrial  
Ethernet and Automation.



**PowerTOP® Xtra.**  
Plugs and connectors  
for toughest conditions.



**Screwless connetions.**  
For CEE plugs,  
connectors and  
receptacles.

For further information please visit our website:

**www.MENNEKES.co.uk**

Request brochures by phone at:

**+44 (0) 16 89 / 83 35 22**

Request brochures by E-Mail to:

**service@MENNEKES.co.uk**

**MENNEKES Electric Ltd.**  
Unit 4, Crayfields Industrial Park  
Main Road, St. Pauls Cray  
Orpington, Kent BR5 3HP, UK  
Phone 0 16 89 / 83 35 22  
Fax 0 16 89 / 83 33 78  
E-Mail [info@MENNEKES.co.uk](mailto:info@MENNEKES.co.uk)  
Internet [www.MENNEKES.co.uk](http://www.MENNEKES.co.uk)

**Headquarters:**  
**MENNEKES**  
**Elektrotechnik GmbH & Co. KG**  
**Industrial plugs and sockets**  
P.O. Box 13 64  
D-57343 Lennestadt  
Phone + 49 (0) 27 23 / 41-1  
Fax + 49 (0) 27 23 / 41-2 14  
E-Mail [info@MENNEKES.de](mailto:info@MENNEKES.de)  
Internet [www.MENNEKES.de](http://www.MENNEKES.de)

**Service by**  
**MENNEKES®.**  
Always well  
informed.